

ERO 25

The modern replacement drive for Eurolift systems

The ERO 25 has been specifically developed to replace the outdated PMS drive in Eurolift elevators. It fits perfectly into existing setups and enables a direct 1:1 replacement without any modifications. Thanks to its energy-efficient belt drive, the ride comfort is maintained – with significantly improved reliability.



Technical data

Encoder: ENDAT ECN1313

Protection class: IP40

Duty cycle: \$5-50%

Brake: 207 VDC

Brake monitoring switch: Microswitch

Suitable for

Schindler Eurolift elevators with PMS drive:

- Modernization projects without machine room
- · Systems with limited space in the shaft head
- Operators seeking an independent alternative to the original manufacturer
- Elevators requiring energy-efficient and quiet drive technology

Drive versions

ERO25 - 450.100

Load capacity: 450 kg **Rated speed:** 1.0 m/s

ERO25 - 1000.100

Load capacity: 1000 kg **Rated speed:** 1.0 m/s

ERO25 - 2000.100

Load capacity: 2000 kg **Rated speed:** 1.0 m/s

ERO25 - 630.100

Load capacity: 630 kg **Rated speed:** 1.0 m/s

ERO25 - 1600.100

Load capacity: 1600 kg **Rated speed:** 1.0 m/s

ERO25 - 2500.100

Load capacity: 2500 kg **Rated speed:** 1.0 m/s





